

DERAPAGE RR 50

ON-ROAD



   [ventmoto.it](https://www.ventmoto.it)

DERAPAGE RR 50

Data sheet

Engine

Type	Minarelli single-cylinder, 2-stroke, liquid-cooled
Displacement	49,7 cm ³
Carburetor	Dell'Orto PHBN 16
Starter	Kick Starter
Clutch	Wet, multiple-disc
Final drive	Chain

Chassis

Frame	Aluminium perimetral frame VENT 6.0, double cradle with removable rear part
Front suspension	USD hydraulic fork Ø 41 mm - preload and rebound adjustable
Rear suspension	Hydraulic monoshock - preload and rebound adjustable with separate gas tank and HM-link 2.0 leverage
Front brake system	Wave disc Ø 300 mm with two piston floating caliper and aluminium oversized brake pump
Rear brake system	Wave disc Ø 220 mm with oversized aluminium floating caliper
Front wheel	100/80-17"
Rear wheel	130/70-17"

Dimensions

Wheelbase	1.445 mm
Seat height	914 mm
Footrest height	360 mm
Fuel tank capacity	9,5 liters
Fuel tank reserve	0,75 liters
Dry weight	95,0 kg



Technical and aesthetic characteristics of the DERAPAGE RR 50 are subject to change without notice.