

DERAPAGE 125 4T DERAPAGE 125 4T LOWRIDE

Engine

| | |
|-----------------|--|
| Engine type | Minarelli single - cylinder, 4 stroke, liquid - cooled |
| Distribution | SOHC, 4-valves with Variable Valve Actuation (VVA) |
| Displacement | 124,7 cm ³ |
| Bore | 52,0 mm |
| Stroke | 58,7 mm |
| Injection | Electronic |
| Ignition system | TCI |
| Starter | Electric |
| Clutch | Wet, multiple-disc |
| Gearbox | 6 speed |
| Final drive | Chain |
| Exhaust system | Euro 5 dual-muffler exhaust system |

Chassis

| | |
|--------------------|--|
| Frame | Steel perimetral frame Vent 6.0, duple cradle with removable rear part |
| Swingarm | Steel |
| Front suspension | USD hydraulic fork Ø 41 mm |
| Front travel | 260 mm |
| Rear suspension | Hydraulic monoshock preload adjustable |
| Rear travel | 240 mm |
| Front brake system | Wave disc Ø 290 mm with two floating piston caliper |
| Rear brake system | Wave disc Ø 220 mm with floating caliper |
| Security systems | Combined Braking System (CBS) |
| Front wheel | 110/70-17" |
| Rear wheel | 140/70-17" |
| Handlebar | Ø 22 mm without crossbar |

Dimensions

| | |
|--------------------------|---------------------------------|
| Length | 2.130 mm |
| Width | 810 mm |
| Height | 1.015 mm |
| Wheelbase | 1.445 mm |
| Steering head angle | 25,5° |
| Seat height | 900 mm (840 mm Lowride version) |
| Footrest height | 315 mm (270 mm Lowride version) |
| Minimum ground clearance | 265 mm (220 mm Lowride version) |
| Fuel tank capacity | 9,5 liters |
| Fuel tank reserve | 1,5 liters |
| Dry weight | 111,0 kg |