

DERAPAGE 50 DERAPAGE 50 LOWRIDE

Engine

Engine type	Minarelli single-cylinder, 2-stroke, liquid-cooled
Displacement	49,7 cm ³
Bore	40,3 mm
Stroke	39 mm
Carburetor	Dell'Orto PHBN 16
Ignition system	Electronic CDI
Starter	Kick Starter
Clutch	Wet, multiple-disc
Gearbox	6 speed
Final drive	Chain
Exhaust system	Euro 5 exhaust system

Chassis

Frame	Steel perimetral frame Vent 6.0, duple cradle with removable rear part
Swingarm	Steel
Front suspension	USD hydraulic fork Ø 41 mm
Front travel	260 mm
Rear suspension	Hydraulic monoshock
Rear travel	300 mm (260 mm versione Lowride)
Front brake system	Wave disc Ø 290 mm with two piston floating caliper
Rear brake system	Wave disc Ø 220 mm with floating caliper
Front wheel	100/90-17"
Rear wheel	130/70-17"
Handlebar	Ø 22 mm without crossbar

Dimensions

Length	2.070 mm
Width	795 mm
Height	1.190 mm
Wheelbase	1.450 mm
Steering head angle	25,5°
Seat height	920 mm (865 mm Lowride version)
Footrest height	345 mm (305 mm Lowride version)
Minimum ground clearance	325 mm (240 mm Lowride version)
Fuel tank capacity	9,5 liters
Fuel tank reserve	0.75 liters
Dry weight	99,0 kg