VENT DERAPAGE 125 RR

Motor

Engine Type	Minarelli single - cylinder, 4 stroke, liquid - cooled
Displacement	124,7 cm³
Bore | Stroke	52,0 mm | 58,7 mm
Injection	Electronic
Ignition System	TCI
Starter	Electric
Clutch	Wet, multiple-disc
Gearbox	6 speed

Frame

Frame	Aluminium perimetral frame Vent 6.1, double cradle with removable rear part
Swingarm	Aluminium
Front Suspension	USD hydraulic fork Ø 41 mm - adjustable preload and rebound
Front Travel	260 mm
Rear Suspension	Hydraulic monoshock, adjustable preload and rebound with separate gas tank and with HM-link 2.0 leverage
Rear Travel	240 mm
Front Brake System	Wave disc Ø 300 mm with aluminium oversized two floating piston caliper and brake pump
Rear Brake System	Wave disc Ø 220 mm with oversized aluminium floating clamper
Security systems	Combined Braking System (CBS)
Front Wheel - Rear Wheel	110/70 17" - 140/70 17"

Dimensions

Length x Width x Height	2.160 x 810 x 1.175 mm
Wheelbase	1.455 mm
Steering Head Angle	25,5°
Seat Height	920 mm
Footrest Height	367 mm
Fuel Tank - Reserve Capacity	9,5 l - 1,5 l
Dry Weight	114 kg

E5+

ventmoto.it

Technical and aesthetic characteristics are subject to change without notice.