VENT

DERAPAGE 50 RR

Motor

Engine Type	Minarelli single-cylinder, 2-stroke, liquid-cooled
Displacement	49,7 cm³
Bore | Stroke	40,3 mm | 39 mm
Carburetor	Dell'Orto PHBN 16
Ignition System	Electronic CDI
Starter	Kick Starter
Clutch	Wet, multiple-disc
Gearbox	6 speed

Frame

Frame	High-strength steel perimeter frame Vent 6.1, double cradle with removable rear section
Swingarm	Aluminium
Front Suspension	USD hydraulic fork Ø 41 mm - adjustable preload and rebound
Front Travel	260 mm
Rear Suspension	Hydraulic monoshock - adjustable preload and rebound with separate gas tank and HM-link 2.0 leverage
Rear Travel	230 mm
Front Brake System	Wave disc Ø 300 mm with two piston floating caliper and aluminium oversized brake pump
Rear Brake System	Wave disc Ø 220 mm with oversized aluminium floating caliper
Front Wheel - Rear Wheel	100/80 17" - 130/70 17"

Dimensions

Length x Width x Height	2.182 x 810 x 1.185 mm
Wheelbase	1.455 mm
Steering Head Angle	25,5°
Seat Height	920 mm
Footrest Height	370 mm
Fuel Tank - Reserve Capacity	9,5 l - 0,75 l
Dry Weight	96 kg

ventmoto.it

Technical and aesthetic characteristics are subject to change without notice.